

- Supported stainless steel crosswind shaft
- Stainless steel ball
- Shielded stainless steel ball bearing

ADDITIONAL FEATURES

101-103-105

- Smooth, dependable drag system: operates by turning drag knob clockwise (with knob facing you) for more pressure, counter-clockwise for less pressure.
- Unscrew housing handle cap and re-install on opposite side of reel.
- and turn handle backward. Remove handle, collar and bearing cover and install those parts in opposite side of reel.
- Convertible folding handle: converts to right or left hand drive in seconds. To convert, hold rotor cup or engage anti-reverse, and turn handle backward. Remove handle, collar and bearing cover and install those parts in opposite side of reel.
- Click on model 101.
- Anti-reverse: silent on models 103 and 105. Soft sounding by flipping down.
- Internal automatic trip with manual override: ball will close on forward rotation of handle. Ball can also be closed manually.

OPERATING FEATURES

101-103-105

MODEL	LINE CAPACITIES (yds./mono)	LINE CAPACITIES (meters/diameter)	GEAR RATIO	WEIGHT (oz.)	WEIGHT (gm.)
101	200 yds-4 lb	183 m-0.19mm	4.9-1	8.6 oz.	244 gm.
103	250 yds-10 lb	206 m-0.32mm	4.3-1	14.4 oz.	408 gm.
105	200 yds-20 lb	183 m-0.48mm	4.1-1	25.8 oz.	730 gm.

101-103-105 SPECIFICATIONS

Penn reels®



101-103-105

SKIRTED SPOOL SPINNING REELS

INSTRUCTION AND PARTS MANUAL

Periodically examine your reel and tighten loose screws and fittings. Depending upon use, your reel should be overhauled at least once every season.

Frrequently lubricate all frictional points. For best results, use Penn Reels lubricant. Penn's tubes of lube are just the ticket for lubricating oil ports and applying a few drops of oil where they will do the most good. Remember, only a few drops of oil are sufficient to do the job. Do not over lubricate!

Periodically examine your reel and tighten loose screws and fittings. Depending upon use, your reel should be overhauled at least once every season.

Periodically examine your reel and tighten loose screws and fittings. Depending upon use, your reel should be overhauled at least once every season.

Frrequently lubricate all frictional points. For best results, use Penn Reels lubricant. Penn's tubes of lube are just the ticket for lubricating oil ports and applying a few drops of oil where they will do the most good. Remember, only a few drops of oil are sufficient to do the job. Do not over lubricate!

Periodically examine your reel and tighten loose screws and fittings. Depending upon use, your reel should be overhauled at least once every season.

Periodically examine your reel and tighten loose screws and fittings. Depending upon use, your reel should be overhauled at least once every season.

CARE AND LUBRICATION

- Anodized aluminum spool with handy line capacity chart and weight
- Die cast aluminum housing and rotor cup for strength and light weight
- Multi-disc drag system for smooth operation and control. Strong, dependable Penn gearing system

HOW TO ORDER PENN REEL PARTS

1. State reel model for which parts are intended.
2. Order parts by name and number.
3. An invoice will then be sent showing parts prices plus shipping and handling charges.
4. Your remittance will then insure prompt shipment.
5. For faster service we suggest you see a local dealer stocking Penn parts.
6. Minimum charge for parts order is \$1.00.

Order Parts Online! ~ We ship to entire USA and some International locations

www.PENNparts.com

LIMITED WARRANTY

Penn Fishing Tackle Mfg. Co. warrants your reel to be free from defects in materials and workmanship for a period of one year from the date of purchase. This warranty does not cover damage or malfunctions caused by accident, abuse or normal expected wear. If your reel has a defect within the terms of the warranty, you should return it to us insured at either address indicated below, and we will repair or replace your reel, at our option, without further cost to you. If, however, we determine after inspection that the repair is not covered by the provisions of this warranty, the reel will be repaired and returned to you at a reasonable charge for labor, parts and return postage.

ALL WARRANTIES WHICH MAY BE IMPLIED BY OPERATION OF LAW INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND WARRANTIES OF FITNESS FOR ANY PARTICULAR PURPOSE, SHALL BE LIMITED TO ONE YEAR FROM THE DATE OF PURCHASE. IN NO EVENT SHALL PENN FISHING TACKLE MFG. CO. BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES FOR BREACH OF THIS WARRANTY OR ANY OTHER WARRANTY WHICH MAY BE IMPLIED BY LAW.

SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, AND SOME STATES DO NOT ALLOW THE EXCLUSION OF CONSEQUENTIAL OR SPECIAL DAMAGES, SO THE ABOVE LIMITATIONS AND/OR EXCLUSION MAY NOT APPLY TO YOU.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

SERVICE OUT OF WARRANTY

Your local Penn dealer can provide fast and convenient service for your Penn reel. You may also return it to Penn for service at either address below. Send it insured and include a short note with your reel stating the problem. To avoid errors, please print your name and address clearly on the package and allow approximately three weeks for Penn to receive, service and return your reel. A reasonable charge will be made for parts, labor and return postage.

PENN FISHING TACKLE MFG. CO. Factory Service Department
3028 W. Hunting Park Avenue
Philadelphia, PA 19132

PENNFISHING TACKLE MFG. CO. Western Warehouse Unit A
550 W. Patrice Place
Gardena, CA 90248

PENN FISHING TACKLE MFG. CO. RESERVES THE RIGHT TO MAKE CHANGES IN PRICES OR SPECIFICATIONS WITHOUT NOTICE.