


#### INTRODUCTION

Congratulations on the purchase of your new Penn Spinfisher® SSg spinning reel. The Penn Spinfisher® SSg is a modernized American classic that boasts of improved durability and smoother performance. Each Spinfisher® SSg is constructed to last due to the highquality components and Penn's 70-plus years of experience building reels.

New features found on the Spinfisher® SSg are highlighted throughout this manual and will help explain the vast improvements and quality enhancements. Also found in this manual are tips for basic maintenance and upkeep of your new fishing red.

The entire company would like to thank you for selecting Penn Reels as your reel of choice. We are confident that your reel will perform for many years.



## SPINFISHER® SSg FEATURES cont.

**Penn Power Drag:** Penn's proven drag performance combines large, smooth friction-washers to dissipate heat and stainless steel metal washers for the smoothest, most durable drag system on the market.

**Lightweight Components:** The housings, rotors and side plates on Spinfisher® SSg Reels are graphite composites for best combination of light weight and strength.

**Heavy Duty, Precision-Cut Gears:** A Spinfisher® tradition, strong, powerful gears, are taken to the next level of performance with new precision-cut gears found in the Spinfisher SSg®. Silky-smooth performance combined with the power and torque necessary for landing large garnefish.

# **SPINNING & FISHING TIPS**

- While fishing and retrieving lures, it is best to keep your rod in an upward position. Your rod will absorb the sudden power of a strike or snag and you will be ready to set the hook when a fish strikes.
- Line twist is a persistent problem inherent in spinning reels due to the rotor spinning line onto the spool. While vast improvements in spinning reel technology have greatly reduced line twist, simply NOT reeling against the drag is the single greatest preventative measure to reduce/eliminate line twist. Reeling against the drag is not tiring out the fish, or getting the fish any closer to the boat. When the fish runs against the drag, stop turning the handle, and allow the drag to play the fish.
- Always try to keep tension on the line when you have a fish on, as slack line will allow the fish to develop the leverage necessary to throw the hook. A tight line works to the angler's favor, and will assist landing most fish.
- When playing a fish, allow the rod to work for you. As the fish is running against the drag, a loaded rod increases the force being applied to the fish, thereby increasing the pressure necessary to swim against the drag. As the fish tires, the angler can pump the rod and turn the handle of the reel to gain line onto the spool
- A full spool of line increase casting distance. Line "slapping", caused by line hitting the spool's upper flange, is typically a sign of an under-filled spool.
- Even under the best conditions, line will become twisted. Cut off all terminal tackle (including snaps, swivels, etc.) and troll just the line behind the boat. This will relax the line and take out the twists. If shore bound, simply feed the line into a current.
- The "working" end of your line (the first 10 feet or so) should be cut back after each fishing trip to ensure there are no nicks, abrasions, etc., in the line.



### CARE AND LUBRICATION

Your Penn Reel is quality manufactured for maximum durability. Like any other precision-made piece of equipment, reasonable care will ensure peak performance and longevity.

After each fishing trip, the reel should be cleaned with a soap solution and fresh water, preferably warm, to remove any accumulated salt deposits.

When washing the reel, use caution not to use a driving force of water, since the water pressure will force salt deposits and/or sand into the reel. A very fine spray will help dissolve the salt on the external parts of the reel and rinse from the reel.

Dry excess moisture from the reel and then sparingly lubricate all exposed areas. A good practice is to spray a rag with a pressurized spray lubricant and wipe down the reels with the rag. Your reel should be stored in a cool, dry place. Do not store in a plastic bag, as condensation may develop.

Periodically examine your reel and tighten loose screws and fittings. Depending upon use, your reel should be overhauled at least once every season.

Frictional points in the reel should be frequently lubricated, and for best results use Penn lubricant. Penn's tubes of lube are the right formula, designed specifically for Penn Reels. Keep in mind, that a few drops of oil is usually sufficient

Major points for external lubrication include: Handle knob, eccentric lever, left and right side bearings, and clicker button.

### **OUT OF WARRANTY SERVICE**

For non-warranty service to your Penn reel, simply return the reel with a brief note describing the service you want performed. Available on the Penn website (www.pennreels.com) is a repair form that we suggest is completed and returned with each reel for more efficient processing. Penn strives to complete all repairs in a timely manner.

Penn will not initiate service until a means of payment is arranged. Accepted means of payment include only the following credit cards: Mastercard, Visa, American Express, and Discover. COD, personal checks, or cash are not accepted.

### SPINFISHER® SSg FEATURES



Techno-Balanced™ Rotor: Wobble-free rotor assembly enhances sensitivity and smoothness. Computer modeling redistributes rotor mass for balanced rotation, resulting in perfect balance and performance.

Infinite Anti-Reverse (IAR): Heavy-Duty Stainless Steel anti-reverse bearing provides instant, infinite anti-reverse, eliminating handle "kick back" for rock solid hook sets and improved smoothness.

Leveline

Leveline™ Spool Wrap System: Penn Leveline™ extends the throw at both extremes of spool oscillation, resulting in a flat, level, line wrap, ideal for all line types including braid.

Stainless Steel Bail Bearings: Five high-quality, shielded, stainless steel ball bearings are incorporated into the Spinfisher SSg. Unlike gimmicky unshielded, bearings that clog with contaminants and salt buildup. Penn's high-grade stainless steel ball bearings were designed for performance in a marine environment. Just remember, high-grade Stainless is better than coated, non-shielded bearings.

Sealed Drag Knob: Water and contaminants are prevented from depositing onto the drag washers courtesy of the sealed drag knob, keeping your drag in peak performance.

Gold Anodized Handle: For improved corrosion resistance, the handle is gold anodized. For convenience, the handle easily converts to right-hand drive for left-handed anglers.

Fall Free Ball Spring: Building upon Penn's already reliable ball system, Penn's Fall Free

Penn Fishing Tackle Mfg. Co., 3028 West Hunting Park Avenue,

bail spring provides consistent and proven performance.

Philadelphia, PA 19132-1121, U.S.A. Telephone: (215) 229-9415

FAX: (215) 223-3017 www.pennreels.com HOW TO ORDER PENN REEL PARTS

406-SSG04 10/04

and 4:30 pm U.S. East Coast time to order your Penn Parts Department at (215) 229-9415 between 8:30 am and 4:30 pm U.S. East Coast time to order your Penn Parts over the telephone. Accepted means of payment include only the following credit cards: Mastercard, Visa, American Express, and Discover. COD, personal checks, or cash are not accepted.

 Penn Parts may also be ordered through Penn's local dealer network. Check your telephone directory for a Penn Dealer near you, or visit Penn's website at www.pennreels.com to locate a nearby dealer.

Penn Fishing Tackle Mfg. Co. reserves the right to discontinue models and make changes in design specifications without notice.

Penn's policy of ongoing research may necessitate design changes for Product performance improvement.

www.PEW parts.com

Scott's Bait &
Tackle
Penn Parts Dept.
945 Radio Road

Tuckerton NJ 08087 (609) 296-1300 No Minimum Order! Plus, Parts in stock that Penn doesn't carry anymore.