

## Penn Reel Parts list for Model: 115L-LH 9/0 Senator, Left Hand

KEY	PART		KEY	PART	
NO	NO.	DESCRIPTION	NO	NO.	DESCRIPTION
1	1-115LH	HANDLE SIDE PLATE (LEFT HAND)	27	27-115	NON-HANDLE SIDE PLATE
2	2-115-O	SIDE PLATE RING-OUTER	28	28-115-l	NON-HANDLE SIDE INNER
2A	2-115-l	HANDLE SIDE RING-INNER	29	29L-115	SPOOL-ALUMINUM
3	3-115LH	BRIDGE W/ SLEEVE (LEFT HAND)	30	30-115	STAND
4	4-115	FIBER WASHER	31	39-12	HANDLE SIDE STAND SCREW (3 REQUIRED)
5	5-115LH	MAIN GEAR (LEFT HAND)	32	32-21	NON-HANDLE SIDE STAND SCREW (3 REQUIRED)
6	6-115	DRAG WASHER (5 REQUIRED)	33	33-340	ROD CLAMP
7	7c-115	METAL DRAG WASHER SET	*	*33R-114	RINGED ROD CLAMP (OPTIONAL)
8A	8-115	TENSION SPRING	34	34-45	CLAMP SCREW (2 REQUIRED)
9	9-114	SPACING SLEEVE	34C	34C-45	ROD CLAMP SCREW W/ NUTS
10	10-114	STAR DRAG WHEEL	35	35-115	CLICK TONGUE
11	11-115	ECCENTRIC JACK	36	36-115	CLICK BUTTON
12	12-114	PINION YOKE	37	37-115	FRAME POST (5 REQUIRED)
13	13-114LH	PINION (LEFT HAND)	38	39-13	NON-HANDLE SIDE POST SCREW (5 REQUIRED)
14	14-116	DOG SPRING	39	39-12	HANDLE SIDE POST SCREW (5 REQUIRED)
15	15-115	DOG	40	40-114H	HANDLE SIDE BEARING
16	16-114	BRIDGE SCREW LOWER (2 REQUIRED)	54	54-114	HARNESS LUG (4 REQUIRED)
17	17-114	BRIDGE SCREW UPPER (2 REQUIRED)	56	56-116	ROD BRACE (ONLY)
18	18-114	CLUTCH SPRING	56C	56C-115	ROD BRACE COMPLETE
19	19-115	ECCENTRIC	98	98-114LH	GEAR SLEEVE (LEFT HAND)
20	20-114	ECCENTRIC SPRING	99	99-115	HOOK SCREW L.H. THREW (2 REQUIRED)
21	21-114	ECCENTRIC LEVER	136	136-115	PRESSURE PLATE WASHER
22	23-60	ECCCENTRIC SCREW	140	140-115	FELT WASHER
23	23-116	HANDLE SCREW	149	149-45	CLAMP NUT (2 REQUIRED)
23A	110-60	HANDLE LOCK SCREW	149A	149-200	HEX NUT (2 REQUIRED)
24	24-115	HANDLE	155	155-115	TURN BUCKLE (2 REQUIRED)
26	26-116	NON-HANDLE SIDE BEARING	165	165-115	HOOK SCREW R.H. THREAD (2 REQUIRED)
			* Not Sh	nown	

NOTE: Many of www.pennparts.com schematics include changes that were either made by Penn, or errors found and corrected by our parts dept. SBT Ver. 021514

PAGE 2 OF 3

## **IMPORTANT NOTE FOR OLDER 115 REELS**

1958 to present day, the 3-115 bridge uses the 23-116 handle nut screw.
Somewhere in between Penn made a design change:
1950 or older reels, the 3-115 bridge used the 23-114 nut screw.
IF your current nut is stamped 23-114, you will need to order the
23-116 nut screw to go with the current version of the bridge.

DESIGN CHANGE 1989 (PLATE/BEARING/SPOOL)	Original system			
Newer 115L bearing System	for reels made prior to 1989			
1-115 NON-HANDLE SIDE Plate (changed)	1-115			
26-116 Bearing w/Cap (pressed into side plate)	26-114 Bearing w/Nut Head			
29L-115 (changed)	29L-115			
The easiest way to see which system your reel has is to look at the handle side bearing.				
The old one has the nut head. The newer one is covered by a cap that is pressed into the plate, almost flush.				

## THESE OLD 1950'S STYLE PARTS ARE NOT AVAILABLE:

- 136 136-117 Collar (old style outer access drags)
- 140 140-117 Felt Washer (old style outer access drags)
- 1 1-115 (50's) Original 115 plate (with outer access hole) a different #26 bearing? See 27 and 29 notes below! We don't know if this older plate also used a different #26 bearing? See 27 and 29 notes below!
- 27 27-115-Early Older still..side plate that used a 40-114 bearing which would NOT work with any of the newer 1 pc spools!
- 29 29M-115 3 pc style metal spool (Instead of smooth sides ramping up, it has a ringed connection at each side of the center spool piece) THE ABOVE 1950'S PARTS ARE NOT INTERCHANGABLE WITH ONES THAT CAME LATER

There were too many changes in size of bearings and the spool shaft

## PAGE 3 OF 3