

Penn Reel Parts list for Model: 650SSm Metal Series

KEY	PUREFISHING	PART		KEY	PUREFISHING	PART	
NO	<u> 7 DIGIT #</u>	NO.	DESCRIPTION	NO	<u>7 DIGIT #</u>	NO.	DESCRIPTION
1	1190841	1-650M	HOUSING	45	1191875	45-650M	HOUSING COVER
6	1180915	6-155	DRAG WASHER HT-100 (2 REQUIRED)	46	1183576	46-750	HOUSING COVER SCREW (4 REQUIRED)
8	1181135	8N-6500	MAIN GEAR	47	1191944	47-650M	SPOOL (COMPLETE)
15 See	HANDLE DESIGN	CHANGES PA	AGE 3	48	1183722	48-750	CLICK TONGUE
19	1181707	19-650M	PINION	48A	1183741	48A-750	CLICK TONGUE WASHER
20	1181790	20-704	BALL BEARING, Pinion Gear	49	1183766	49-710	CLICK TONGUE SPRING
20A	1181789	20-6500	BALL BEARING, Main Gear/Housing	50	1183766	50-712	BAIL SPRING COVER SCREW
21	1192639	21-750M	BEARING COVER	51	1183794	51-650	RETAINING RING
22 See	SPOOL CLICK SO	CREW info belo	ow w	52	1183831	52N-650N	DRAG KNOB
23	1181953	23-750	LOCKING PLATE SCREW	56T	1183917	56T-650	DRAG WASHER, TEFLON
24	1182056	24-650M	BAIL WIRE	57	1183936	57-650	DRAG WASHER (KEYED) LARGE DIA (2 REQUIRED)
27	1182270	27-650M	ROTOR	58	1183959	58-650	DRAG WASHER (OCTAGON) (2 REQUIRED)
31	1182679	31-750M	BAIL ARM SCREW	60	1192063	60-750M	THRUST WASHER
31A	1182689	31A-550G	BAIL CAM SCREW	95B	1184312	95B-70	ROTOR LOCKING PLATE
32	1182740	32-750M	BAIL ARM SPRING	98	1192202	98-750M	CLUTCH HOUSING
34	1182833	34-750M	BAIL ARM	98C SEE	Clutch Bearing P.	AGE 3	
34A	1182847	34A-750	BAIL ARM BUSHING	132	1184596	132-750M	ROLLER WASHER
34B	1182848	34B-750M	PIVOT PLATE	225	1185007	225-750	SPOOL SHAFT BUSHING
34C	1191657	34C-750M	PIVOT ARM	226	1192464	226-750M	REAR CAP
35	1191677	35-750M	LINE ROLLER	227	1192487	22 <mark>7-750</mark> M	BAIL SPRING COVER
35A	1182965	35A-8500J	BALL BEARING (2 REQUIRED)	231	1185092	2 <mark>31</mark> -650M	CROSSWIND GEAR
36	1183016	36 <mark>-75</mark> 0	BAIL STUD SCREW	233	1185145	233-55 <mark>0G</mark>	BEARING COVER (CLOSED)
36A	1183032	36A-750	LOCK WASHER	236	1192531	236-750M	TRIP BUMPER
38	1183157	38-710	ROTOR NUT	**	NLA	237-650SSm	Decal, Housing ("Penn 650SSm")
39	1183228	39-65 <mark>0</mark> M	SPOOL SHAFT	**	NLA	238-650SSm	Dec <mark>al, Housing (Ree</mark> l Speed)
43, 44C	, 43A SEE Cross	vind Bloc <mark>k d</mark> es	si <mark>gn chang</mark> e below	**	NLA	240-650SSm	Decal, Spoo <mark>l (Line Capacity)</mark>
44	1183462	44-750	TRIP BUMPER SCREW				
44A	1183459	44-710	CLU <mark>TCH HOUSING SCR</mark> EW (3 REQUIRED)	•	** not shown on s	schematic	

SPOOL CLICK SCREW CHANGED

22 1181922 22-750 SPOOL CLICK SCREW w/straight pan head (EARLY REELS)

1186969 48B-750M SPOOL CLICK SCREW w/phillips flat head (LATER REELS) LOWER PROFILE

SCREWS 4-40X .187 LONG -- SCREWS APPEAR TO BE INTERCHANGEABLE BUT THE PHILLIPS HEAD SITS LOWER

KEY PUREFISHING PART

NO 7 DIGIT# NO. DESCRIPTION NO 7 DIGIT# NO. DESCRIPTION

Crosswind Block Design Change

ORIGINAL DESIGN SINGLE SCREW

43 1183406 43-750M CROSSWIND BLOCK ORIGINAL 44B 1183454 44-560 SCREW FOR CW BLOCK

43A 43A-750 NLA CROSSWIND BLOCK PLATE ORIGINAL

> This design screws a single screw through the block into the shaft.

It puts too much pressure on the shaft.

NOTE: 39-650M spool shaft is still currently coming in with the hole for the screw in the shaft.

Eventually, Penn will be releasing shafts with no holes in them.

You can add strength to the existing 43-750M crosswind block by adding

the 44-750 screws with the 43A-750 plate.

CLUTCH BEARING ASSEMBLY (aka A/R Bearing)

98B NLA 98B-5600 **BEARING** 98C 1184384 98C-750M **CLUTCH BEARING ASSEMBLY**

98S NLA 98S-750M **CLUTCH BEARING SLEEVE**

98C ASSEMBLY REPLACES 98B and 98S

HANDLE DESIGN CHANGED

15	NLA	15-650M	HANDLE ASSEMBLY Gen 1 + 2	15	1181491	15N-650M	HANDLE ASSEMBLY GEN 3
**	NLA	15 <mark>-65</mark> 0M-H	HANDLE Sub assembly	**	1191149	15-750M-H	HANDLE Sub assembly
15B	NLA	1 <mark>5B-750M</mark>	DUAL PIVOT	15B	N/A	15B- ??	DUAL PIVOT thicker than on old handle (NOT SERVICABLE)
15C		15C ??	PIVOT SCREW, UNKNOWN #	15C		15C ??	PIVOT SCREW, UNKNOWN #
16	NLA	16-75 <mark>0</mark> M	COLLAR	16	N/A	16- ??	SWOOPING COLLAR (NOT SERVICABLE)

KEY

43

44C

43A

PUREFISHING

1183406

1183462

1183427

PART

43N-750M

43A-750N

This is actually the same

design as the older SS reels,

More strength in the shaft this way

44-750

CROSSWIND BLOCK, NEWER

CROSSWIND SCREW (2 REQUIRED)

CROSSWIND BLOCK PLATE, NEWER

NEWER DESIGN DUAL SCREWS

3 Generations of Cosmetic Changes to the HANDLE

15-650M GEN 1 Flat plain rubberized knob and straight line angled outward collar

15-650M GEN 2 Flat rubberized knob WITH GRIP and <mark>straight line a</mark>ngled outward collar

15N-650M GEN 3 Flat rubberized knob WITH GRIP and swooping to outward lip collar

Parts non-servicable or design changed

27E 1191470 27E-750M **BALANCE WEIGHT**

27E was on the rev 0 schematic but removed after rev 5?

63 NLA 63-750 SPOOL BUSHING

MYSTIC REEL PARTS REVISION!

NOTE: Many of www.mysticparts.com schematics include changes that were either made by Penn, or errors found and corrected by our parts dept. MRP Ver 101922 (BASED ON PENN'S REV. 6 4-4-12)

63 was on the rev 0 schematic but has never been available